

Homework 2

Due: 15 February 2021

Problem 2.1

Consider the task of writing functions

```
bool anyEmpty (shared_ptr<Link<string>> list)
bool allEmpty (shared_ptr<Link<string>> list)
```

that determine whether any of the strings in a given linked list are empty strings (i.e. ""), and whether *all* of the strings in a given linked list are empty strings.

For the moment I'm more interested in the algorithm, so you're better off writing it out by hand (and I won't fuss over things like semicolons). You should still test your work by tracing it on a concrete example!

Problem 2.2

Consider the following code, which assumes that the relevant item type is `int`:

```
shared_ptr<Link<int>> a = make_shared<Link<int>>(5, nullptr);
shared_ptr<Link<int>> b = make_shared<Link<int>>(8,
        make_shared<Link<int>>(13,
        make_shared<Link<int>>(21, a)));
a->setNext(b);
```

Draw a diagram of memory after those statements are executed, and describe as specifically as you can why that state of affairs can cause problems. Also comment on how you could detect inside a program if this type of thing had happened.

(Hint: think back to Lab 4, and specifically about what happened with the line `shared_ptr<Link<int>> d = c;` and how `==` worked with pointers.)

Collaboration policy: group work! If you work with other people on this homework, hand in one copy and put all your names on top. There will be a revision cycle for this.

Handing in: on paper in class is fine; otherwise scan/screenshot/photograph into a *single* file and hand in on Canvas. Either way, one handin per group, please.